


FAG

129-TVH

Self-aligning ball bearing

Self-aligning ball bearing 12...TVH, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Bore type	Z	Cylindrical
Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	9 mm	Bore diameter
D	26 mm	Outside diameter
B	8 mm	Width
C _r	3.950 N	Basic dynamic load rating, radial
C _{0r}	810 N	Basic static load rating, radial
C _{ur}	51 N	Fatigue load limit, radial
n _G	33.500 1/min	Limiting speed
n _{gr}	24.100 1/min	Reference speed
≈m	21,2 g	Masa

Mounting dimensions

d _{a min}	13,2 mm	Minimum diameter shaft shoulder
D _{a max}	21,8 mm	Maximum diameter of housing shoulder
r _{a max}	0,6 mm	Maximum fillet radius



Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
D ₁	20 mm	Shoulder diameter outer ring
d ₁	14,5 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,94	Dynamic axial load factor
Y ₂	3,01	Dynamic axial load factor
Y ₀	2,04	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna