



FAG

16040-MA-C3

Deep groove ball bearing

Deep groove ball bearing 160..-MA, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	MA	Solid brass cage, outer ring guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	310 mm	Outside diameter
B	34 mm	Width
C _r	186.000 N	Basic dynamic load rating, radial
C _{0r}	202.000 N	Basic static load rating, radial
C _{ur}	7.500 N	Fatigue load limit, radial
n _G	3.700 1/min	Limiting speed
n _{gr}	2.470 1/min	Reference speed
≈m	10,5 kg	Masa



Mounting dimensions

$d_{a\ min}$	208,8 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	301,2 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2 mm	Minimum chamfer dimension
D_1	277,3 mm	Shoulder diameter outer ring
d_1	244,35 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

f_0	16,4	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia