



FAG

16056-M-C4

Deep groove ball bearing

Deep groove ball bearing 160..-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	420 mm	Outside diameter
B	44 mm	Width
C _r	243.000 N	Basic dynamic load rating, radial
C _{0r}	330.000 N	Basic static load rating, radial
C _{ur}	10.400 N	Fatigue load limit, radial
n _G	2.700 1/min	Limiting speed
n _{gr}	1.800 1/min	Reference speed
≈m	23,2 kg	Masa



Mounting dimensions

$d_{a \min}$	292,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	407,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
D_1	370,55 mm	Shoulder diameter outer ring
d_1	329,95 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	16,5	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe