



FAG



21322-E1-XL-K-TVPB-C3

Spherical Roller Bearing

Spherical roller bearings 213...E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E1           | Without central rip               |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | TVPB         | Plastic cage                      |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication feature     | Standard     |                                   |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 110 mm      | Bore diameter                     |
| D               | 240 mm      | Outside diameter                  |
| B               | 50 mm       | Width                             |
| C <sub>r</sub>  | 600.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 640.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 70.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 2.700 1/min | Reference speed                   |
| ≈m              | 10,661 kg   | Masa                              |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 124 mm | Minimum diameter shaft shoulder       |
| $D_{a \max}$ | 226 mm | Maximum diameter of housing shoulder  |
| $r_{a \max}$ | 2,5 mm | Maximum recess radius                 |
| $B_{a \min}$ | 9 mm   | Minimum cavity width of the sleeve    |
| $d_{a \max}$ | 146 mm | Maximum diameter of shaft shoulder    |
| $d_{b \min}$ | 118 mm | Minimum cavity diameter of the sleeve |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 3 mm     | Minimum chamfer dimension          |
| $D_1$      | 202,5 mm | Bore diameter outer ring           |
| $d_2$      | 146,4 mm | Raceway diameter of the inner ring |
| $d_s$      | 6,3 mm   | Diameter lubrication hole          |
| $n_s$      | 12,2 mm  | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,21 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 3,24 | Dynamic axial load factor                                                            |
| $Y_2$ | 4,82 | Dynamic axial load factor                                                            |
| $Y_0$ | 3,16 | Static axial load factor                                                             |

### Additional information

|        |                   |
|--------|-------------------|
| H322   | Adapter sleeve    |
| AHX322 | Withdrawal sleeve |



## Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna