


FAG

# 2206-2RS-TVH>N

Self-aligning ball bearing

Self-aligning ball bearing 22..-2RS-TVH, seals, plastic cage

## Informacje techniczne







### Twoja aktualna wersja produktu

| | | |
|---|---|---|
| Version code | >N | Not marked on bearing |
| Bore type | Z | Cylindrical |
| Sealing | 2RS | Contact seal on both sides |
| Cage | TVH | Solid cage made of glass-fiber reinforced polyamide PA66 |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Lubricant | GA14 | Ball bearing grease, low noise |

### Main Dimensions & Performance Data

| | | |
|---|---|---|
| d | 30 mm | Bore diameter |
| D | 62 mm | Outside diameter |
| B | 20 mm | Width |
| $C_r$ | 15.900 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 4.650 N | Basic static load rating, radial |
| $C_{ur}$ | 295 N | Fatigue load limit, radial |
| $n_G$ | 7.100 1/min | Limiting speed |
| ≈m | 265 g | Masa |

### Mounting dimensions

| | | |
|---|---|---|
| $d_{a\ min}$ | 35,6 mm | Minimum diameter shaft shoulder |
| $D_{a\ max}$ | 56,4 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 1 mm | Maximum fillet radius |

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

## Dimensions

| | | |
|---|---|---|
| $r_{min}$ | 1 mm | Minimum chamfer dimension |
| $D_1 \approx$ | 51,56 mm | Shoulder diameter outer ring |
| $D_2 \approx$ | 53,33 mm | Caliber diameter outer ring |
| $d_1 \approx$ | 39,55 mm | Shoulder diameter inner ring |
| $d_2 \approx$ | 37,3 mm | Caliber diameter inner ring |

## Temperature range

| | | |
|---|---|---|
| $T_{min}$ | -20 °C | Operating temperature min. |
| $T_{max}$ | 100 °C | Operating temperature max. |

## Calculation factors

| | | |
|---|---|---|
| e | 0,25 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,54 | Dynamic axial load factor |
| $Y_2$ | 3,93 | Dynamic axial load factor |
| $Y_0$ | 2,66 | Static axial load factor |

## Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Obciążenie osiowe dwukierunkowe
- Smarowanie dożywotnie, bezobsługowe
- Smarowanie smarem
- Uszczelnienie dwustronne
- Nieosiowość statyczna
- Nieosiowość dynamiczna

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje