



FAG

22319-E1-XL-K-C4

Spherical Roller Bearing

Spherical roller bearings 223...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne




Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E1           | Without central rip               |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | JPA          | Sheet metal cage                  |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication feature     | Standard     |                                   |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 95 mm       | Bore diameter                     |
| D               | 200 mm      | Outside diameter                  |
| B               | 67 mm       | Width                             |
| C <sub>r</sub>  | 670.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 700.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 61.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 3.700 1/min | Limiting speed                    |
| n <sub>gr</sub> | 2.800 1/min | Reference speed                   |
| ≈m              | 9,677 kg    | Masa                              |





Mounting dimensions

|                    |        |                                       |
|--------------------|--------|---------------------------------------|
| d <sub>a min</sub> | 109 mm | Minimum diameter shaft shoulder       |
| d <sub>a max</sub> | 115 mm | Maximum diameter of shaft shoulder    |
| D <sub>a max</sub> | 186 mm | Maximum diameter of housing shoulder  |
| r <sub>a max</sub> | 2,5 mm | Maximum recess radius                 |
| d <sub>b min</sub> | 105 mm | Minimum cavity diameter of the sleeve |
| B <sub>a min</sub> | 7 mm   | Minimum cavity width of the sleeve    |

Dimensions

|                  |          |                                    |
|------------------|----------|------------------------------------|
| r <sub>min</sub> | 3 mm     | Minimum chamfer dimension          |
| D <sub>1</sub>   | 171,2 mm | Bore diameter outer ring           |
| d <sub>2</sub>   | 116 mm   | Raceway diameter of the inner ring |
| d <sub>s</sub>   | 6,3 mm   | Diameter lubrication hole          |
| n <sub>s</sub>   | 12,2 mm  | Width of lubricating groove        |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,33 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 2,03 | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 3,02 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 1,98 | Static axial load factor                                                         |

Additional information

|         |                   |
|---------|-------------------|
| H2319   | Adapter sleeve    |
| AHX2319 | Withdrawal sleeve |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna