





FAG


23060-BE-XL-H40AB-C3

Spherical Roller Bearing

Spherical roller bearing 230...-BE-XL-H40AB, symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	H40AB	6 lubricating holes at the inner ring

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	460 mm	Outside diameter
B	118 mm	Width
C _r	2.160.000 N	Basic dynamic load rating, radial
C _{0r}	3.450.000 N	Basic static load rating, radial
C _{ur}	305.000 N	Fatigue load limit, radial
n _G	1.570 1/min	Limiting speed
n _{gr}	980 1/min	Reference speed
≈m	69,31 kg	Masa



Mounting dimensions

d _{a min}	314,6 mm	Minimum diameter shaft shoulder
D _{a max}	445,4 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius

Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	413 mm	Bore diameter outer ring
d ₂	340 mm	Raceway diameter of the inner ring
d _s	9,5 mm	Diameter lubrication hole
n _s	17,7 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,92	Dynamic axial load factor
Y ₂	4,35	Dynamic axial load factor
Y ₀	2,86	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna