



FAG


23084-BEA-XL-MB1-H151

Spherical Roller Bearing

Spherical roller bearing 230...-BEA-XL-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                                      |              |                                       |
|--------------------------------------|--------------|---------------------------------------|
| Design                               | BEA          | With lose center lip ring             |
| Bore type                            | Z            | Cylindrical                           |
| Cage                                 | MB1          | Solid brass cage                      |
| Radial internal clearance            | CN (Group N) | Normal internal clearance             |
| Relubrication feature                | Standard     |                                       |
| Locating feature, bearing outer ring | H151         | 1 Locking feature, bearing outer ring |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 420 mm      | Bore diameter                     |
| D               | 620 mm      | Outside diameter                  |
| B               | 150 mm      | Width                             |
| C <sub>r</sub>  | 3.650.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.300.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 520.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.090 1/min | Limiting speed                    |
| n <sub>gr</sub> | 650 1/min   | Reference speed                   |
| m               | 153,5 kg    | Masa                              |



Mounting dimensions

|                    |        |                                 |
|--------------------|--------|---------------------------------|
| d <sub>a min</sub> | 438 mm | Minimum diameter shaft shoulder |
| D <sub>a max</sub> | 602 mm |                                 |
| r <sub>a max</sub> | 4 mm   | Maximum recess radius           |

Dimensions

|                  |          |                             |
|------------------|----------|-----------------------------|
| r <sub>min</sub> | 5 mm     | Minimum chamfer dimension   |
| D <sub>1</sub>   | 560,7 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 12,5 mm  | Diameter lubrication hole   |
| n <sub>s</sub>   | 23,5 mm  | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                           |
|----------------|------|---------------------------|
| e              | 0,21 |                           |
| Y <sub>1</sub> | 3,17 | Dynamic axial load factor |
| Y <sub>2</sub> | 4,72 | Dynamic axial load factor |
| Y <sub>0</sub> | 3,1  | Static axial load factor  |



## Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna