



FAG



231/560-BEA-XL-MB1-H40

Spherical Roller Bearing

Spherical roller bearing 231...-BEA-XL-MB1-H40, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	560 mm	Bore diameter
D	920 mm	Outside diameter
B	280 mm	Width
C _r	9.700.000 N	Basic dynamic load rating, radial
C _{0r}	16.400.000 N	Basic static load rating, radial
C _{ur}	1.060.000 N	Fatigue load limit, radial
n _G	630 1/min	Limiting speed
n _{gr}	300 1/min	Reference speed
≈m	740,5 kg	Masa

Mounting dimensions

d _{a min}	592 mm	Minimum diameter shaft shoulder
D _{a max}	888 mm	
r _{a max}	6 mm	Maximum recess radius



Dimensions

r _{min}	7,5 mm	Minimum chamfer dimension
D ₁	806,6 mm	Bore diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,29	
Y ₁	2,32	Dynamic axial load factor
Y ₂	3,45	Dynamic axial load factor
Y ₀	2,26	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna