FAG

X-life

# 23152-BE-XL-C3

Spherical Roller Bearing

Spherical roller bearing 231..-BE-XL,
symmetric with rib washer

## Informacje techniczne







### Twoja aktualna wersja produktu

| | | |
|---|---|---|
| Design | BE | With lose center lip ring |
| Bore type | Z | Cylindrical |
| Cage | JPB | Sheet metal cage |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication | Standard | |

### Main Dimensions & Performance Data

| | | |
|---|---|---|
| d | 260 mm | Bore diameter |
| D | 440 mm | Outside diameter |
| B | 144 mm | Width |
| $C_r$ | 2.600.000 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 3.900.000 N | Basic static load rating, radial |
| $C_{ur}$ | 310.000 N | Fatigue load limit, radial |
| $n_G$ | 1.500 1/min | Limiting speed |
| $n_{\vartheta r}$ | 860 1/min | Reference speed |
| ≈m | 87,58 kg | Masa |

### Mounting dimensions

| | | |
|---|---|---|
| $d_{a\ min}$ | 277 mm | Minimum diameter shaft shoulder |
| $D_{a\ max}$ | 423 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 3 mm | Maximum recess radius |

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

## Dimensions

| | | |
|---|---|---|
| $r_{min}$ | 4 mm | Minimum chamfer dimension |
| $D_1$ | 382,7 mm | Bore diameter outer ring |
| $d_2$ | 301,7 mm | Raceway diameter of the inner ring |
| $d_s$ | 9,5 mm | Diameter lubrication hole |
| $n_s$ | 17,7 mm | Width of lubricating groove |

## Temperature range

| | | |
|---|---|---|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 200 °C | Operating temperature max. |

## Calculation factors

| | | |
|---|---|---|
| e | 0,32 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,12 | Dynamic axial load factor |
| $Y_2$ | 3,15 | Dynamic axial load factor |
| $Y_0$ | 2,07 | Static axial load factor |

## Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Obciążenie osiowe dwukierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia
- Łożysko gabarytowe
- Nieosiowość statyczna
- Nieosiowość dynamiczna

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje