

FAG


23234-E1-XL-TVPB

Spherical Roller Bearing

Spherical roller bearings 232...-E1, main dimensions to DIN 635-2

X-life

Informacje techniczne




Twoja aktualna wersja produktu

|                           |              |                           |
|---------------------------|--------------|---------------------------|
| Design                    | E1           | Without central rip       |
| Bore type                 | Z            | Cylindrical               |
| Cage                      | TVPB         | Plastic cage              |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication feature     | Standard     |                           |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 170 mm      | Bore diameter                     |
| D               | 310 mm      | Outside diameter                  |
| B               | 110 mm      | Width                             |
| C <sub>r</sub>  | 1.640.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 2.170.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 168.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.090 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.160 1/min | Reference speed                   |
| ≈m              | 34,522 kg   | Masa                              |





### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a\ min}$ | 187 mm | Minimum diameter shaft shoulder      |
| $D_{a\ max}$ | 293 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 3 mm   | Maximum recess radius                |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 4 mm     | Minimum chamfer dimension          |
| $D_1$      | 267,4 mm | Bore diameter outer ring           |
| $d_2$      | 199,8 mm | Raceway diameter of the inner ring |
| $d_s$      | 8 mm     | Diameter lubrication hole          |
| $n_s$      | 15 mm    | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,33 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,03 | Dynamic axial load factor                                                            |
| $Y_2$ | 3,02 | Dynamic axial load factor                                                            |
| $Y_0$ | 1,98 | Static axial load factor                                                             |



## Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna