



FAG

23938-S-MB-C3

Spherical Roller Bearing

Spherical roller bearings 239, main dimensions to DIN 635-2

Informacje techniczne



Twoja aktualna wersja produktu

Bore type	Z	Cylindrical
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	S	With 3 lubricating holes and groove

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	260 mm	Outside diameter
B	52 mm	Width
C _r	470.000 N	Basic dynamic load rating, radial
C _{0r}	890.000 N	Basic static load rating, radial
C _{ur}	64.000 N	Fatigue load limit, radial
n _G	3.150 1/min	Limiting speed
n _{gr}	1.750 1/min	Reference speed
≈m	8,09 kg	Masa

Mounting dimensions

d _{a min}	198,8 mm	Minimum diameter shaft shoulder
D _{a max}	251,2 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius



Dimensions

r_{min}	2 mm	Minimum chamfer dimension
D_1	240,2 mm	Bore diameter outer ring
d_s	4,8 mm	Diameter lubrication hole
n_s	9,5 mm	Width of lubricating groove

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,18	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,66	Dynamic axial load factor
Y_2	5,46	Dynamic axial load factor
Y_0	3,58	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna