

FAG



24044-BE-XL-K30-C4

Spherical Roller Bearing

Spherical roller bearings 240...-BE-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	K30	Tapered, taper 1:30
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	340 mm	Outside diameter
B	118 mm	Width
C _r	1.620.000 N	Basic dynamic load rating, radial
C _{0r}	2.600.000 N	Basic static load rating, radial
C _{ur}	260.000 N	Fatigue load limit, radial
n _G	1.830 1/min	Limiting speed
n _{gr}	1.090 1/min	Reference speed
≈m	37,7 kg	Masa



Mounting dimensions

d _{a min}	232,4 mm	Minimum diameter shaft shoulder
D _{a max}	327,6 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	295,7 mm	Bore diameter outer ring
d ₂	245 mm	Raceway diameter of the inner ring
d _s	6,3 mm	Diameter lubrication hole
n _s	12,2 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,1	Dynamic axial load factor
Y ₂	3,13	Dynamic axial load factor
Y ₀	2,06	Static axial load factor

Additional information

AH24044	Withdrawal sleeve
---------	-------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna