

FAG



**24136-BE-XL-C3**

## Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,  
symmetric with rib washer

X-life

## Informacje techniczne



## Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BE           | With lose center lip ring         |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | JPB          | Sheet metal cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication feature     | Standard     |                                   |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 180 mm      | Bore diameter                     |
| D               | 300 mm      | Outside diameter                  |
| B               | 118 mm      | Width                             |
| C <sub>r</sub>  | 1.460.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 2.170.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 208.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 980 1/min   | Reference speed                   |
| ≈m              | 33,2 kg     | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 194 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 286 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,5 mm | Maximum recess radius                |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 3 mm     | Minimum chamfer dimension          |
| $D_1$      | 255,7 mm | Bore diameter outer ring           |
| $d_2$      | 204,8 mm | Raceway diameter of the inner ring |
| $d_s$      | 6,3 mm   | Diameter lubrication hole          |
| $n_s$      | 12,2 mm  | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,36 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 1,86 | Dynamic axial load factor                                                            |
| $Y_2$ | 2,77 | Dynamic axial load factor                                                            |
| $Y_0$ | 1,82 | Static axial load factor                                                             |



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna