

FAG


24144-BE-XL-K30-C4

Spherical Roller Bearing

Spherical roller bearings 241...-BE-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	K30	Tapered, taper 1:30
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	370 mm	Outside diameter
B	150 mm	Width
C _r	2.190.000 N	Basic dynamic load rating, radial
C _{0r}	3.250.000 N	Basic static load rating, radial
C _{ur}	300.000 N	Fatigue load limit, radial
n _G	1.650 1/min	Limiting speed
n _{gr}	750 1/min	Reference speed
≈m	62,25 kg	Masa



Mounting dimensions

$d_{a\ min}$	237 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	353 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	314,3 mm	Bore diameter outer ring
d_2	247,6 mm	Raceway diameter of the inner ring
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,74	Dynamic axial load factor
Y_2	2,59	Dynamic axial load factor
Y_0	1,7	Static axial load factor

Additional information

AH24144	Withdrawal sleeve
---------	-------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna