

FAG



24148-BE-XL-H40

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL-H40, symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	400 mm	Outside diameter
B	160 mm	Width
C _r	2.600.000 N	Basic dynamic load rating, radial
C _{0r}	3.900.000 N	Basic static load rating, radial
C _{ur}	340.000 N	Fatigue load limit, radial
n _G	1.470 1/min	Limiting speed
n _{gr}	650 1/min	Reference speed
≈m	78,82 kg	Masa



Mounting dimensions

$d_{a\ min}$	257 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	383 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius

Dimensions

$r_{\ min}$	4 mm	Minimum chamfer dimension
D_1	339 mm	Bore diameter outer ring
d_2	267,3 mm	Raceway diameter of the inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,71	Dynamic axial load factor
Y_2	2,54	Dynamic axial load factor
Y_0	1,67	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna