FAG

29324-E1-XL

Axial spherical roller bearing

Axial spherical roller bearing 293..-E1-XL, no flanging ring

X-life

Informacje techniczne







Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	Without	
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	210 mm	Outside diameter
T	54 mm	Height
C_a	800.000 N	Basic dynamic load rating, axial
C_{0a}	2.210.000 N	Basic static load rating, axial
C_{ua}	290.000 N	Fatigue load limit, axial
n_G	3.350 1/min	Limiting speed
$n_{\vartheta r}$	1.700 1/min	Reference speed
≈m	7 kg	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{a\ min}$	165 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	182 mm	Maximum diameter of housing shoulder
$D_{b\ min}$	213 mm	Minimum bore diameter housing
$d_{b\ max}$	129 mm	Maximum distance sleeve
$r_{a\ max}$	2,1 mm	Maximum recess radius

Dimensions

D_1	154 mm	Bore diameter housing washer
d_1	192,6 mm	Rip diameter shaft washer
r_{min}	2,1 mm	Minimum chamfer dimension
T_1	27 mm	Height of the housing washer
T_3	34 mm	Height of the shaft washer
T_5	48 mm	Distance shaft washer - cage
A	70 mm	Distance of the center point

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia
- Nieosiowość statyczna
- Nieosiowość dynamiczna

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje