



**3004-2RS-C3**

Angular contact ball bearing

Angular contact ball bearing 30...-B-2RS-TVH,
double row, seals, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	42 mm	Outside diameter
B	16 mm	Width
C _r	14.300 N	Basic dynamic load rating, radial
C _{0r}	9.400 N	Basic static load rating, radial
C _{ur}	490 N	Fatigue load limit, radial
n _G	10.500 1/min	Limiting speed
m	0,091 kg	Masa



Mounting dimensions

d a min	23,2 mm	Minimum diameter shaft shoulder
D a max	38,8 mm	Maximum diameter of housing shoulder
r a max	0,6 mm	Maximum fillet radius

Dimensions

r min	0,6 mm	Minimum chamfer dimension
D 1	35 mm	Shoulder diameter outer ring
D 2	36,38 mm	Caliber diameter outer ring
d 1	27,1 mm	Shoulder diameter inner ring
d 2	25,31 mm	Caliber diamter inner ring
a	21,1 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T min	-20 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne