



FAG





3213-BD-XL

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL,
double row, X-life, steel sheet metal cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	Without	Not sealed
Cage	JH	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	120 mm	Outside diameter
B	38,1 mm	Width
C _r	86.000 N	Basic dynamic load rating, radial
C _{0r}	77.000 N	Basic static load rating, radial
C _{ur}	5.300 N	Fatigue load limit, radial
n _G	5.700 1/min	Limiting speed
n _{gr}	6.000 1/min	Reference speed
≈m	1,62 kg	Masa



Mounting dimensions

$d_{a\ min}$	74 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	111 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1,5 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	1,5 mm	Minimum chamfer dimension
$D_{\ 1}$	106,64 mm	Shoulder diameter outer ring
$D_{\ 2}$	110,13 mm	Caliber diameter outer ring
$d_{\ 1}$	87,7 mm	Shoulder diameter inner ring
$d_{\ 2}$	85,28 mm	Caliber diamter inner ring
a	70,7 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia