



FAG

32334

Tapered roller bearing

Tapered roller bearings 323, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	360 mm	Outside diameter
B	120 mm	Width, inner ring
C	100 mm	Width, outer ring
T	127 mm	Width, total
C _r	1.640.000 N	Basic dynamic load rating, radial
C _{0r}	2.550.000 N	Basic static load rating, radial
C _{ur}	285.000 N	Fatigue load limit, radial
n _G	1.870 1/min	Limiting speed
n _{gr}	1.090 1/min	Thermal speed rating
≈m	59,5 kg	Masa



Mounting dimensions

d a max	208 mm	Maximum diameter of shaft shoulder
d b min	187 mm	Minimum diameter of shaft shoulder
D a min	295 mm	Minimum diameter of housing shoulder
D a max	341 mm	Maximum diameter of housing shoulder
D b min	335 mm	Minimum diameter of housing shoulder
C a min	12 mm	Minimum axial space
C b min	27 mm	Minimum axial space
r a max	5 mm	Maximum fillet radius of shaft
r b max	4 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	5 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	4 mm	Minimum chamfer dimension of outer ring back face
a	90 mm	Distance between the apexes of the pressure cones
d 1	256 mm	Guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	200 °C	Operating temperature max.

Calculation factors

e	0,36	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,67	Dynamic axial load factor
Y 0	0,92	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe