3806-2RS

Angular contact ball bearing

Angular contact ball bearing 38..-B-2RS-TVH,
double row, seals, plastic cage

Informacje techniczne





Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	42 mm	Outside diameter
B	10 mm	Width
C_r	6.100 N	Basic dynamic load rating, radial
C_{0r}	6.000 N	Basic static load rating, radial
C_{ur}	320 N	Fatigue load limit, radial
n_G	8.100 1/min	Limiting speed
≈m	0,037 kg	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{a\ min}$	32 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	40 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,3 mm	Maximum fillet radius

Dimensions

r_{min}	0,3 mm	Minimum chamfer dimension
$D_1 \approx$	37,96 mm	Shoulder diameter outer ring
$D_2 \approx$	38,99 mm	Caliber diameter outer ring
$d_1 \approx$	34 mm	Shoulder diameter inner ring
$d_2 \approx$	32,92 mm	Caliber diameter inner ring
$a \approx$	20,2 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Obciążenie osiowe dwukierunkowe
- Smarowanie dożywotnie, bezobsługowe
- Smarowanie smarem
- Uszczelnienie dwustronne

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje