





FAG

6001-C-C4>V

Deep groove ball bearing

Deep groove ball bearing 60...-C, single row,
Generation C, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Type of Seal	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	28 mm	Outside diameter
B	8 mm	Width
C _r	5.900 N	Basic dynamic load rating, radial
C _{0r}	2.370 N	Basic static load rating, radial
C _{ur}	164 N	Fatigue load limit, radial
n _G	42.500 1/min	Limiting speed
n _{gr}	26.000 1/min	Reference speed
≈m	0,021 kg	Masa



Mounting dimensions

d a min	14 mm	Minimum diameter shaft shoulder
D a max	26 mm	Maximum diameter of housing shoulder
r a max	0,3 mm	Maximum fillet radius

Dimensions

r min	0,3 mm	Minimum chamfer dimension
D 1	23,34 mm	Shoulder diameter outer ring
D 2	25,1 mm	Caliber diameter outer ring
d 1	16,66 mm	Shoulder diameter inner ring
d 2	15,69 mm	Caliber diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

f 0	13,1	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia