



FAG

6010-2Z

Deep groove ball bearing

Deep groove ball bearing 60...-2Z, single row, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	80 mm	Outside diameter
B	16 mm	Width
C _r	22.000 N	Basic dynamic load rating, radial
C _{0r}	15.800 N	Basic static load rating, radial
C _{ur}	800 N	Fatigue load limit, radial
n _G	10.400 1/min	Limiting speed
n _{gr}	8.900 1/min	Reference speed
≈m	0,262 kg	Masa



Mounting dimensions

$d_{a\ min}$	54,6 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	75,4 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	1 mm	Minimum chamfer dimension
$D_{\ 1}$	70,2 mm	Shoulder diameter outer ring
$D_{\ 2}$	72,94 mm	Caliber diameter outer ring
$d_{\ 1}$	59,75 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-20 °C	Operating temperature min.
$T_{\ max}$	120 °C	Operating temperature max.

Calculation factors

$f_{\ 0}$	15,6	Calculation factor
-----------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne