



FAG

6334-M

Deep groove ball bearing

Deep groove ball bearing 63...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                          |
|----------------------------------|--------------|------------------------------------------|
| Sealing                          | Without      | Not sealed                               |
| Cage                             | M            | Solid brass cage, rolling element guided |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                    |
| Dimensional / heat stabilization | S1           | Rings dimensional stabilized up to 200°  |
| Lubricant                        | Without      | Bearing not greased                      |
| Radial internal clearance        | CN (Group N) | Normal internal clearance                |
| Bore type                        | Z            | Cylindrical                              |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 170 mm      | Bore diameter                     |
| D               | 360 mm      | Outside diameter                  |
| B               | 72 mm       | Width                             |
| C <sub>r</sub>  | 325.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 365.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 15.100 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 3.200 1/min | Limiting speed                    |
| n <sub>gr</sub> | 2.600 1/min | Reference speed                   |
| ≈m              | 43 kg       | Masa                              |



Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a\ min}$ | 187 mm | Minimum diameter shaft shoulder      |
| $D_{a\ max}$ | 343 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 3 mm   | Maximum fillet radius                |

Dimensions

|             |           |                              |
|-------------|-----------|------------------------------|
| $r_{\ min}$ | 4 mm      | Minimum chamfer dimension    |
| $D_{\ 1}$   | 298 mm    | Shoulder diameter outer ring |
| $d_{\ 1}$   | 232,62 mm | Shoulder diameter inner ring |

Temperature range

|             |        |                            |
|-------------|--------|----------------------------|
| $T_{\ min}$ | -30 °C | Operating temperature min. |
| $T_{\ max}$ | 200 °C | Operating temperature max. |

Calculation factors

|           |      |                    |
|-----------|------|--------------------|
| $f_{\ 0}$ | 13,9 | Calculation factor |
|-----------|------|--------------------|

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Łożysko gabarytowe                |