



FAG



X-life

7217-B-XL-MP

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-MP,
single row, X-life, solid brass cage

Informacje techniczne

Twoja aktualna wersja produktu

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	28 mm	Width
C _r	93.000 N	Basic dynamic load rating, radial
C _{0r}	81.000 N	Basic static load rating, radial
C _{ur}	5.200 N	Fatigue load limit, radial
n _G	7.700 1/min	Limiting speed
n _{gr}	4.800 1/min	Reference speed
≈m	2 kg	Masa



Mounting dimensions

d a min	96 mm	Minimum diameter of shaft shoulder
D a max	139 mm	Maximum diameter of housing shoulder
D b max	144,4 mm	Maximum diameter of housing shoulder
r a max	2 mm	Maximum fillet radius of shaft
r a1 max	1 mm	Maximum fillet radius of housing

Dimensions

r min	2 mm	Minimum chamfer dimension
r 1 min	1 mm	Minimum chamfer dimension
D 1	125 mm	Shoulder diameter on outer ring wide side face
d 1	110,6 mm	Shoulder diameter on inner ring wide side face
a	63,3 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia