FAG

7303-B-XL-2RS-TVP

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Design variant	B	B
Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA14	Ball bearing grease, low noise

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	47 mm	Outside diameter
B	14 mm	Width
C_r	18.700 N	Basic dynamic load rating, radial
C_{0r}	9.000 N	Basic static load rating, radial
C_{ur}	620 N	Fatigue load limit, radial
n_G	9.800 1/min	Limiting speed
≈m	107 g	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{a\ min}$	22,6 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	41,4 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	42,8 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	0,6 mm	Maximum fillet radius of housing

Dimensions

r_{min}	1 mm	Minimum chamfer dimension
$r_{1\ min}$	0,6 mm	Minimum chamfer dimension
D_1	35,54 mm	Shoulder diameter on outer ring wide side face
D_2	37,2 mm	Caliber diameter on outer ring wide side face
D_3	42,63 mm	Caliber diameter on outer ring small side face
d_1	29,19 mm	Shoulder diameter on inner ring wide side face
d_2	26,13 mm	Caliber diameter on inner ring wide side face
a	20,4 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Właściwości

- F_r Obciążenie promieniowe
- F_a Obciążenie osiowe jednokierunkowe
- L_h Smarowanie dożywotnie, bezobsługowe
- Smarowanie smarem
- Uszczelnienie dwustronne

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje