



FAG


7330-B-MP-UO

Angular contact ball bearing

Angular contact ball bearing 73..-B-MP, single row, solid brass cage



Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	65 mm	Width
C _r	340.000 N	Basic dynamic load rating, radial
C _{0r}	430.000 N	Basic static load rating, radial
C _{ur}	14.600 N	Fatigue load limit, radial
n _G	3.150 1/min	Limiting speed
n _{gr}	2.200 1/min	Reference speed
≈m	25,4 kg	Masa



Mounting dimensions

d a min	167 mm	Minimum diameter of shaft shoulder
D a max	303 mm	Maximum diameter of housing shoulder
D b max	311 mm	Maximum diameter of housing shoulder
r a max	3 mm	Maximum fillet radius of shaft
r a1 max	1,5 mm	Maximum fillet radius of housing

Dimensions

r min	4 mm	Minimum chamfer dimension
r 1 min	1,5 mm	Minimum chamfer dimension
D 1	255,8 mm	Shoulder diameter on outer ring wide side face
d 1	218,3 mm	Shoulder diameter on inner ring wide side face
a	131,1 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T min	-30 °C	Operating temperature min.
T max	200 °C	Operating temperature max.

Additional information

Tol (+)	12 μm	Tolerance for axial clearance or preload per set
A min	0 mm	Axial clearance per set min.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe