

**KBS25-PP**

## Linear Ball Bearing

Linear ball bearings KBS.-PP, machined range, adjustable, sealed on all sides, corrosion-resistant design possible

## Informacje techniczne

## Twoja aktualna wersja produktu

|      |    |
|------|----|
| Size | 25 |
|------|----|

## Main Dimensions &amp; Performance Data

|                    |          |                     |
|--------------------|----------|---------------------|
| F <sub>w</sub>     | 25 mm    | Bore diameter       |
| D                  | 40 mm    | Outside diameter    |
| L                  | 58 mm    | Length              |
|                    | h12      | Tolerance           |
| C <sub>min</sub>   | 2.800 N  | Load capacity dyn.  |
| C <sub>0 min</sub> | 2.220 N  | Load capacity stat. |
| C <sub>max</sub>   | 2.950 N  | Load capacity dyn.  |
| C <sub>0 max</sub> | 2.850 N  | Load capacity stat. |
| ≈m                 | 184,05 g | Masa                |

## Mounting dimensions

|                 |         |                      |
|-----------------|---------|----------------------|
| L <sub>2</sub>  | 43,7 mm |                      |
|                 | H13     | Tolerance            |
| B <sub>L2</sub> | 1,85 mm |                      |
| B <sub>3</sub>  | 1 mm    |                      |
| D <sub>N</sub>  | 37,5 mm |                      |
| N <sub>2</sub>  | 2,5 mm  |                      |
| X               | 62 °    |                      |
|                 | 6       | Number of rows balls |

