




FAG

NJ2320-E-XL-MPAX-ILR-C4

Cylindrical roller bearing

Cylindrical roller bearing NJ...E...MPAX-ILR, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	215 mm	Outside diameter
B	73 mm	Width
C _r	840.000 N	Basic dynamic load rating, radial
C _{0r}	720.000 N	Basic static load rating, radial
C _{ur}	125.000 N	Fatigue load limit, radial
n _G	5.600 1/min	Limiting speed
n _{gr}	2.500 1/min	Reference speed
≈m	13,32 kg	Masa

Mounting dimensions

d _{a min}	114 mm	Minimum diameter shaft shoulder
d _{a max}	125 mm	Maximum diameter of shaft shoulder
D _{a max}	201 mm	Maximum diameter of housing shoulder



Dimensions

r _{min}	3 mm	Minimum chamfer dimension
r _{1 min}	3 mm	Minimum chamfer dimension
s	4,2 mm	Axial displacement
E	191,5 mm	Raceway diameter outer ring
F	127,5 mm	Raceway diameter inner ring
D _{1 min}	181,95 mm	Minimum rib diameter outer ring
d ₁	139,4 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe