



FAG

NJ320-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	215 mm	Outside diameter
B	47 mm	Width
C _r	450.000 N	Basic dynamic load rating, radial
C _{0r}	425.000 N	Basic static load rating, radial
C _{ur}	72.000 N	Fatigue load limit, radial
n _G	5.600 1/min	Limiting speed
n _{gr}	3.350 1/min	Reference speed
≈m	8,7 kg	Masa



Mounting dimensions

d _a min	114 mm	Minimum diameter shaft shoulder
d _a max	125 mm	Maximum diameter of shaft shoulder
D _a max	201 mm	Maximum diameter of housing shoulder
d _c min	143 mm	Minimum shaft shoulder

r_a max 2,5 mm Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
r _{1 min}	3 mm	Minimum chamfer dimension
s	1,2 mm	Axial displacement
E	191,5 mm	Raceway diameter outer ring
F	127,5 mm	Raceway diameter inner ring
D _{1 min}	181,95 mm	Minimum rib diameter outer ring
d ₁	139,4 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ320-E L-washer

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia