




FAG

NJ412-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Informacje techniczne



Twoja aktualna wersja produktu

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	150 mm	Outside diameter
B	35 mm	Width
C _r	211.000 N	Basic dynamic load rating, radial
C _{0r}	184.000 N	Basic static load rating, radial
C _{ur}	33.500 N	Fatigue load limit, radial
n _G	8.600 1/min	Limiting speed
n _{gr}	4.800 1/min	Reference speed
≈m	3,45 kg	Masa



Mounting dimensions

d _{a min}	74 mm	Minimum diameter shaft shoulder
d _{a max}	82 mm	Maximum diameter of shaft shoulder
D _{a max}	136 mm	Maximum diameter of housing shoulder
d _{c min}	94 mm	Minimum shaft shoulder
r _{a max}	2 mm	Maximum recess radius

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	2,1 mm	Minimum chamfer dimension
s	3,4 mm	Axial displacement
E	127 mm	Raceway diameter outer ring
F	83 mm	Raceway diameter inner ring
D _{1 min}	119,5 mm	Minimum rib diameter outer ring
d ₁	91,6 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ412	L-washer
-------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia