NKIA5908-XL

Needle roller/angular contact ball bearing

Informacje techniczne



Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	62 mm	Outside diameter
B	30 mm	Width
C_r	48.500 N	Basic dynamic load rating, radial
C_{0r}	67.000 N	Basic static load rating, radial
C_a	9.200 N	Basic dynamic load rating, axial
C_{0a}	19.400 N	Basic static load rating, axial
C_{ur}	11.700 N	Fatigue limit load, radial
C_{ur}	11.700 N	Fatigue load limit, radial
C_{ua}	880 N	Fatigue load limit, axial
n_G	9.600 1/min	Limiting speed
$n_{\vartheta r}$	7.500 1/min	Reference speed
≈m	314,79 g	Masa

Dimensions

F	48 mm	Raceway diameter inner ring
r_{min}	0,6 mm	Minimum chamfer dimension

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia
- Mała przestrzeń zabudowy

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje