



FAG

NU252-E-M1A [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne

Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	480 mm	Outside diameter
B	80 mm	Width
C _r	1.350.000 N	Basic dynamic load rating, radial
C _{0r}	1.890.000 N	Basic static load rating, radial
C _{ur}	142.000 N	Fatigue load limit, radial
n _G	2.100 1/min	Limiting speed
n _{gr}	1.110 1/min	Reference speed
≈m	69,5 kg	Masa



Mounting dimensions

$d_{a \min}$	280 mm	Minimum diameter shaft shoulder
$d_{a \max}$	314 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	320 mm	Minimum shaft shoulder
$D_{a \max}$	460 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$r_{a1 \max}$	4 mm	Maximum recess radius

Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$r_1 \min$	5 mm	Minimum chamfer dimension
s	6,2 mm	Axial displacement
E	429 mm	Raceway diameter outer ring
F	317 mm	Raceway diameter inner ring
$D_1 \min$	406,6 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia