FAG

NU419-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NU..-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design



Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	240 mm	Outside diameter
B	55 mm	Width
C_r	495.000 N	Basic dynamic load rating, radial
C_{0r}	470.000 N	Basic static load rating, radial
C_{ur}	59.000 N	Fatigue load limit, radial
n_G	5.200 1/min	Limiting speed
$n_{\vartheta r}$	3.200 1/min	Reference speed
≈m	13,893 kg	Masa



Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{a\ min}$	115 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	132 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	136 mm	Minimum shaft shoulder
$D_{a\ max}$	220 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius
$r_{a1\ max}$	3 mm	Maximum recess radius

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
$r_{1\ min}$	4 mm	Minimum chamfer dimension
s	5,2 mm	Axial displacement
E	201,5 mm	Raceway diameter outer ring
F	133,5 mm	Raceway diameter inner ring
$D_{1\ min}$	189,7 mm	Minimum rib diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Właściwości

Obciążenie promieniowe

Smarowanie smarem

Smarowanie olejem

Bez uszczelnienia

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje