



FAG


NUP226-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NUP..-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Informacje techniczne





Twoja aktualna wersja produktu

|                           |              |                                  |
|---------------------------|--------------|----------------------------------|
| Design                    | E            | Increased Capacity Design        |
| Cage                      | TVP2         | Solid Window Cage made from PA66 |
| Radial internal clearance | CN (Group N) | Normal internal clearance        |
| Tolerance class           | PN           | Normal (ISO 492:2023)            |
| Number of rows            | 1            | Single-row design                |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 130 mm      | Bore diameter                     |
| D               | 230 mm      | Outside diameter                  |
| B               | 40 mm       | Width                             |
| C <sub>r</sub>  | 425.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 445.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 71.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 2.800 1/min | Reference speed                   |
| ≈m              | 6,53 kg     | Masa                              |





Mounting dimensions

|         |          |                                      |
|---------|----------|--------------------------------------|
| d 1     | 164 mm   | Maximum rib diameter inner ring      |
| D 1 min | 201,2 mm | Minimum rib diameter outer ring      |
| d a min | 144 mm   | Minimum diameter shaft shoulder      |
| d c min | 168 mm   | Minimum shaft shoulder               |
| D a max | 216 mm   | Maximum diameter of housing shoulder |
| r a max | 2,5 mm   | Maximum recess radius                |

Dimensions

|         |          |                             |
|---------|----------|-----------------------------|
| r min   | 3 mm     | Minimum chamfer dimension   |
| r 1 min | 3 mm     | Minimum chamfer dimension   |
| E       | 209,5 mm | Raceway diameter outer ring |
| F       | 153,5 mm | Raceway diameter inner ring |
| B 3     | 6 mm     | Width of loose rib          |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -30 °C | Operating temperature min. |
| T max | 120 °C | Operating temperature max. |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |