

PSHE50-XL-N

Plummer block housing unit

Plummer block housing units PSHE, cast iron housing, radial insert ball bearing with eccentric locking collar, P seals

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Groove	N	Cast iron housing with undercut slot for end caps
Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	50 mm	Bore diameter
L	135 mm	Length total
H_2	115 mm	Height
≈m	2,25 kg	Masa

Mounting dimensions

J	101,6 mm	Distance fixing bore
K	M16	Thread fixing bore

Dimensions

H	57,2 mm	Distance shaft axis
A	54 mm	Width (base)
A_1	34 mm	Width (head)
Q	M6	Connection thread for lubrication
S_1	32,8 mm	Distance of raceway to locking collar

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Additional information

	SHE10	Housing
	GRAE50-XL-NPP-B	Bearing designation
	KASK10	Protecting cap

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje