


**RAE30-XL-NPP-B-FA106** [🔗](#)

Radial insert ball bearing

Radial insert ball bearing RAE...XL-NPP-B

X-life

Informacje techniczne

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
D _{SP}	62 mm	Outside diameter
B	23,8 mm	Width
C _{0r}	11.300 N	Basic static load rating, radial
C _{ur}	480 N	Fatigue load limit, radial
B ₁	35,8 mm	Locking collar total width
C _r	19.500 N	Basic dynamic load rating, radial
≈m	0,32 kg	Masa

Dimensions

C	18 mm	Width, outer ring
S	9 mm	Distance raceway
d ₂	37,4 mm	Rib diameter sealing inner ring
d ₃	44 mm	Outside diameter locking collar/locknut
W	4 mm	Width of flats

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości

-  F_r Obciążenie promieniowe
-  F_a Obciążenie osiowe jednokierunkowe
-  F_a Obciążenie osiowe dwukierunkowe
-  L_h Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna