

RALE30-XL-NPP-B

Radial insert ball bearing

Radial insert ball bearings RALE..-NPP-B, spherical outer ring, location by eccentric locking collar, P seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	30 mm	Bore diameter
B_1	26,5 mm	Locking collar total width
C_r	13.200 N	Basic dynamic load rating, radial
C_{0r}	8.300 N	Basic static load rating, radial
C_{ur}	430 N	Fatigue load limit, radial
≈m	0,18 kg	Masa

Dimensions

C	13 mm	Width, outer ring
S	6,5 mm	Distance raceway
d_3	42,5 mm	Outside diameter locking collar/locknut
W	2,5 mm	Width of flats
B	18,5 mm	Width

Calculation factors

f_0	14,8	Calculation factor

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Właściwości

Obciążenie promieniowe

Obciążenie osiowe jednokierunkowe

Obciążenie osiowe dwukierunkowe

Smarowanie dożywotnie, bezobsługowe

Smarowanie smarem

Uszczelnienie dwustronne

Nieosiowość statyczna

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje