

RASEY90-XL

Plummer block housing unit

Plummer block housing units RASEY, cast iron housing, radial insert ball bearing with grub screws in inner ring, R seals

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	90 mm	Bore diameter
L	330 mm	Length total
H_2	200 mm	Height
≈m	12,39 kg	Masa

Mounting dimensions

J	268 mm	Distance fixing bore
N	27 mm	Width (slot)
N_1	35 mm	Length (slot)

Dimensions

H	101,6 mm	Distance shaft axis
A	85 mm	Width (base)
A_1	55 mm	Width (head)
H_1	35 mm	Height (base)
B	96 mm	Width
S_1	56,3 mm	Distance of raceway to locking collar
Q	M6	Connection thread for lubrication

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Additional information

	ASE18	Housing
	GYE90-XL-KRR-B	Bearing designation

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje