




RCJY65-214-XL

Flanged housing unit

Housing units RCJY, four-bolt flanged housing units, cast iron, grub screws in inner ring, R seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	65 mm	Bore diameter
L	188 mm	Flange width
U	82,4 mm	Total height unit
C _r	66.000 N	Basic dynamic load rating, radial
C _{0r}	44.000 N	Basic static load rating, radial
C _{ur}	1.870 N	Fatigue load limit, radial

≈m	5,86 kg	Masa
----	---------	------

Mounting dimensions

J	150 mm	Distance fixing bore
N	18 mm	Fixing bore

n	4	Number of screwing holes
---	---	--------------------------



Dimensions

A	52 mm	Height housing
A ₁	18 mm	Thickness of flange
A ₂	38 mm	Distance raceway
B	74,6 mm	Width
V	165 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication

Additional information

1	Number of housings
GEHCJ14-GG	Housing
GYE65-214-XL-KRR-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.