



FAG

S693>N

Deep groove ball bearing

Deep groove ball bearing S69, corrosion-resistant materials, single row, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	3 mm	Bore diameter
D	8 mm	Outside diameter
B	3 mm	Width
C _r	590 N	Basic dynamic load rating, radial
C _{0r}	180 N	Basic static load rating, radial
C _{ur}	11,1 N	Fatigue load limit, radial
n _G	102.000 1/min	Limiting speed
n _{gr}	54.000 1/min	Reference speed
m	0,6 g	Masa



Mounting dimensions

$d_{a\min}$	3,8 mm	Minimum diameter shaft shoulder
$D_{a\max}$	7,2 mm	Maximum diameter of housing shoulder
$r_{a\max}$	0,15 mm	Maximum fillet radius

Dimensions

$r_{\min}$	0,15 mm	Minimum chamfer dimension
D_1	6,7 mm	Shoulder diameter outer ring
d_1	5,3 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	11,9	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Ochrona przed korozją