


SL024976-A-C3

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	380 mm	Bore diameter
D	520 mm	Outside diameter
B	140 mm	Width
C _r	2.250.000 N	Basic dynamic load rating, radial
C _{0r}	5.500.000 N	Basic static load rating, radial
C _{ur}	590.000 N	Fatigue load limit, radial
n _G	680 1/min	Limiting speed
n _{gr}	325 1/min	Reference speed
≈m	90,55 kg	Masa

Mounting dimensions

d _{c min}	430,5 mm	Minimum shaft shoulder
d _{a min}	430,2 mm	Minimum diameter shaft shoulder
D _{e min}	481 mm	Minimum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
s	7 mm	Axial displacement
C	70 mm	Distance to lubrication hole
d _{1 max}	430,2 mm	Maximum rib diameter inner ring
E	481,35 mm	Raceway diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

NNCL4976V	Bearing designation DIN5412
-----------	-----------------------------

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	łożysko gabarytowe