

**SL045056-D-PP**

Cylindrical roller bearing

Cylindrical roller bearing SL04...-D-PP, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

Informacje techniczne

Twoja aktualna wersja produktu

Design	D	New outer Contour
Sealing	PP	Contact Seal on both sides
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	420 mm	Outside diameter
B	190 mm	Width
C_r	2.600.000 N	Basic dynamic load rating, radial
C_{0r}	5.200.000 N	Basic static load rating, radial
C_{ur}	590.000 N	Fatigue load limit, radial
n_G Grease	450 1/min	Limiting speed for grease lubrication
$\approx m$	87,8 kg	Masa



Mounting dimensions

C _{a1}	154 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C _{a2}	149 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d ₁	321 mm	Rib diameter inner ring
d ₂	354 mm	Sealing diameter (rib)
d ₃	453 mm	Outside diameter of snap ring WRE
d _{1 min}	321,5 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

Dimensions

C	189 mm	Width, outer ring
C ₁	163,2 mm	Distance ring grooves
D ₁	413 mm	Diameter of groove
m	7,3 mm	Width of groove
r _{min}	1,1 mm	Minimum chamfer dimension
t	3 mm	Chamfer width
X	150 mm	Distance between rolling elements

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Łożysko gabarytowe