

SL182230-A-BR-C3

Cylindrical roller bearing

Cylindrical roller bearing SL1822..-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design



Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	270 mm	Outside diameter
B	73 mm	Width
C_r	820.000 N	Basic dynamic load rating, radial
C_{0r}	1.160.000 N	Basic static load rating, radial
C_{ur}	154.000 N	Fatigue load limit, radial
n_G	1.560 1/min	Limiting speed
$n_{\vartheta r}$	1.130 1/min	Reference speed
≈m	17,9 kg	Masa



Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{a\ min}$	185,5 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	185,5 mm	Minimum shaft shoulder
$D_{a\ max}$	225 mm	Maximum diameter of housing shoulder
$D_{e\ min}$	237 mm	Minimum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius
E	237,4 mm	Raceway diameter outer ring

Dimensions

r_{min}	3 mm	Minimum chamfer dimension
s	6 mm	Axial displacement
d_1	185,5 mm	Maximum rib diameter inner ring
$D_{1\ min}$	225,2 mm	Minimum rib diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje