



SL182996-TB-BR

Cylindrical roller bearing

Cylindrical roller bearing SL1829..-TB, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                             |
|---------------------------|--------------|---------------------------------------------|
| Design                    | TB           | Bearings with increased axial load capacity |
| Radial internal clearance | CN (Group N) | Normal internal clearance                   |
| Tolerance class           | PN           | Normal (ISO 492:2023)                       |
| Number of rows            | 1            | Single-row design                           |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 480 mm      | Bore diameter                     |
| D               | 650 mm      | Outside diameter                  |
| B               | 100 mm      | Width                             |
| C <sub>r</sub>  | 2.390.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 4.800.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 480.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 530 1/min   | Limiting speed                    |
| n <sub>gr</sub> | 280 1/min   | Reference speed                   |
| ≈m              | 92,4 kg     | Masa                              |



Mounting dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| d <sub>a min</sub> | 538 mm   | Minimum diameter shaft shoulder      |
| d <sub>c min</sub> | 538 mm   | Minimum shaft shoulder               |
| D <sub>a max</sub> | 596,5 mm | Maximum diameter of housing shoulder |
| D <sub>e min</sub> | 614,5 mm | Minimum diameter of housing shoulder |
| r <sub>a max</sub> | 5 mm     | Maximum recess radius                |
| E                  | 614,8 mm | Raceway diameter outer ring          |

Dimensions

|                    |          |                                 |
|--------------------|----------|---------------------------------|
| r <sub>min</sub>   | 5 mm     | Minimum chamfer dimension       |
| s                  | 7 mm     | Axial displacement              |
| d <sub>1</sub>     | 538 mm   | Maximum rib diameter inner ring |
| D <sub>1 min</sub> | 596,6 mm | Minimum rib diameter outer ring |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Łożysko gabarytowe                |