




SL183034-A

Cylindrical roller bearing

Cylindrical roller bearing SL18...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	260 mm	Outside diameter
B	67 mm	Width
C _r	700.000 N	Basic dynamic load rating, radial
C _{0r}	1.050.000 N	Basic static load rating, radial
C _{ur}	135.000 N	Fatigue load limit, radial
n _G	1.480 1/min	Limiting speed
n _{gr}	1.120 1/min	Reference speed
≈m	11,794 kg	Masa



Mounting dimensions

$d_{a\min}$	198,1 mm	Minimum diameter shaft shoulder
$d_{c\min}$	198 mm	Minimum shaft shoulder
$D_{a\max}$	232,5 mm	Maximum diameter of housing shoulder
$D_{e\min}$	243,5 mm	Minimum diameter of housing shoulder
$r_{a\max}$	2,1 mm	Maximum recess radius
E	243,6 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
s	7 mm	Axial displacement
d_1	198,1 mm	Maximum rib diameter inner ring
$D_1\min$	232,7 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia