

SL183064-TB-BR-C3

Cylindrical roller bearing

Cylindrical roller bearing SL1830..-TB ,full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design





Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	480 mm	Outside diameter
B	121 mm	Width
C_r	2.080.000 N	Basic dynamic load rating, radial
C_{0r}	3.450.000 N	Basic static load rating, radial
C_{ur}	345.000 N	Fatigue load limit, radial
n_G	770 1/min	Limiting speed
$n_{\vartheta r}$	480 1/min	Reference speed
≈m	71,52 kg	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{a\ min}$	369,5 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	369,5 mm	Minimum shaft shoulder
$D_{a\ max}$	430 mm	Maximum diameter of housing shoulder
$D_{e\ min}$	449,5 mm	Minimum diameter of housing shoulder
$r_{a\ max}$	4 mm	Maximum recess radius
E	449,5 mm	Raceway diameter outer ring

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
s	14 mm	Axial displacement
d_1	369,5 mm	Maximum rib diameter inner ring
$D_{1\ min}$	430,1 mm	Minimum rib diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia
- Łożysko gabarytowe

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje