

SL185052-TB-C3-2S

Cylindrical roller bearing

Cylindrical roller bearing SL1850..-TB,full complement roller set, two-row, semi-locating bearing, 1 rib on outer ring, 3 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design



Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	400 mm	Outside diameter
B	190 mm	Width
C_r	2.750.000 N	Basic dynamic load rating, radial
C_{0r}	5.000.000 N	Basic static load rating, radial
C_{ur}	580.000 N	Fatigue load limit, radial
n_G	940 1/min	Limiting speed
$n_{\vartheta r}$	490 1/min	Reference speed
≈m	79,5 kg	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Mounting dimensions

$d_{c\ min}$	304 mm	Minimum shaft shoulder
$d_{a\ min}$	304 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	360 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	4 mm	Maximum recess radius
$D_{e\ min}$	358 mm	Minimum diameter of housing shoulder

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
$r_{1\ min}$	4 mm	Minimum chamfer dimension
s	11 mm	Axial displacement
C	95 mm	Distance to lubrication hole
d_1	304 mm	Maximum rib diameter inner ring
$D_{1\ min}$	358 mm	Minimum rib diameter outer ring
E	376 mm	Raceway diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia
- Łożysko gabarytowe

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje