




SL192317
Cylindrical roller bearing

Informacje techniczne



Twoja aktualna wersja produktu

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	180 mm	Outside diameter
B	60 mm	Width
C _r	500.000 N	Basic dynamic load rating, radial
C _{0r}	610.000 N	Basic static load rating, radial
C _{ur}	88.000 N	Fatigue load limit, radial
n _G	2.410 1/min	Limiting speed
n _{gr}	1.710 1/min	Reference speed
m	7,152 kg	Masa



Dimensions

D ₁	150,9 mm	Shoulder diameter outer ring
D _{a max}	150,5 mm	Maximum diameter of housing shoulder
d ₁	118,2 mm	Shoulder diameter inner ring
d _{a min}	107 mm	Minimum diameter shaft shoulder
d _{c min}	118 mm	Minimum shaft shoulder
F	107 mm	Raceway diameter inner ring
r _{a max}	3 mm	Maximum fillet radius
r _{min}	3 mm	Minimum chamfer dimension
s	4 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia