


SL192324-TB-XL-BR [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

Informacje techniczne



Twoja aktualna wersja produktu

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	260 mm	Outside diameter
B	86 mm	Width
C _r	1.130.000 N	Basic dynamic load rating, radial
C _{0r}	1.230.000 N	Basic static load rating, radial
C _{ur}	203.000 N	Fatigue load limit, radial
n _G	1.940 1/min	Limiting speed
n _{gr}	1.120 1/min	Reference speed
m	22,3 kg	Masa



Dimensions

D ₁	213,1 mm	Shoulder diameter outer ring
D _{a max}	213 mm	Maximum diameter of housing shoulder
d ₁	164,2 mm	Shoulder diameter inner ring
d _{a min}	147 mm	Minimum diameter shaft shoulder
d _{c min}	164 mm	Minimum shaft shoulder
F	147,4 mm	Raceway diameter inner ring
r _{a max}	3 mm	Maximum fillet radius
r _{min}	3 mm	Minimum chamfer dimension
s	5 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia